

Electric Minibus

The Nexport 7.5m electric minibus is one of the few electric minibuses available for school, on-demand, tourist transfer and shuttle transport – that is also DDA compliant.

The bus has a capacity of 30 (25 seated plus 5 standees) in route service configuration or 25 (all seater) in private charter configuration.

Reaching 240km in a single charge from its 178kWh LFP battery it can be charged back to full capacity in 2 hours.

Sleek design with no batteries on the roof

Greater aerodynamic stability

Safer cornering due to low center of gravity


Simple to operate, easy to drive


Roomier and brighter interior cabin

Ergonomically designed driver cabin

Comprehensive aftercare & warranty package

Electric Minibus – Technical specifications & features





Route service configuration

All seater configuration

Dimensions (L X W X H) mm	67495 X 2370 X 2950
Wheelbase (mm) + Overhang (Front mm/Rear mm)	4550 + 1100/1845
Minimum Ground Clearance/Turning Radius	>200/<=17
Approach/Departure Angle (Deg)	-
Curb Weight/Gross Vehicle Mass (kg)	6250/9500
Battery Type (OEM/Chemistry)	CALB/LFP
Battery Capacity (kWh)/Range (kms)	178/240
Battery Cooling	Integrated with A/C system
Standard Voltage (V)	627.9
Charge Rate (kWh)	180
Charging System/Location	CCS2 DC/LHS (RHS or front is optional extra)
Drive System	DANA motor MD90-E+Controller: Rated/Peak power 101/170kWh
Maximum Torque (NM) - Rated/Peak	680/1900
Standard Safety inclusions	Lane Departure Warning, Forward and Pedestrian Collision Warning, Headway Monitoring Alert, Speed Limit Warning, CCTV and Fire Suppression Systems
Optional Safety Features	Driver Monitoring System, Blind Spot Monitoring, 360° Camera, Intelligent High Beam and Speed Adaptation
Rear Axle Type	Independent suspension
Load Capacity	6.5T
Front Axle Type	GK Drive BFA80I
Load Capacity	3.5T
Tyre Size	215/75R17.5
Wheel	17.5x6.0, Aluminium alloy
Suspension Type	Front 2, rear 2 air suspension, ELC
Brake Type	Disc brake
Regenerative Braking	Standard
EBS	Standard
ABS	Standard

